



Rust Reconverter LT

RUST CONVERTER
& PROTECTIVE COATING / PRIMER

**ŚRODEK DO PRZEMIANY RDZY
I POWŁOKA OCHRONNA / PODKŁAD**

Rust Reconverter LT przedłuża żywotność wszelkich elementów wykonanych z metali żelaznych lub ich stopów. Usuwa rdzę i pozostawia ochronną warstwę podkładową – wszystko w jednym szybkim i łatwym kroku!

Rust Reconverter LT powstrzymuje dalsze rdzewienie maszyn, narzędzi, pojazdów, sprzętu, łodzi, konstrukcji metalowych i nie tylko. Koniec ze skrobaniem i malowaniem zardzewiałego metalu! RUST RECONVERTER LT chemicznie przekształca rdzę w czarny kompleks organiczny, tworząc jednocześnie na powierzchni przezroczystą powłokę akrylową. W przypadku stosowania wewnątrz pomieszczeń powłoka może utrzymywać się przez lata, nawet bez malowania. W przypadku stosowania na zewnątrz lub w warunkach wysokiej wilgotności należy pokryć ją farbą emaliową na bazie oleju lub farbą epoksydową. Wydajność wynosi około 50 metrów kwadratowych na galon. Sama powłoka wystarcza na lata, ale stanowi również doskonały podkład pod farby lateksowe, epoksydowe i olejne.

Idealny do:

- Każdej zardzewiałej powierzchni z metalu żelaznego, którą można pomalować
- Statki i łodzie robocze
- Urządzenia i obiekty do uzdatniania wody oraz oczyszczania ścieków
- Komercyjne baseny i ośrodki wypoczynkowe
- Systemy HVAC
- Konstrukcje metalowe i budynki

Karta charakterystyki : <https://workdrive.zohoexternal.com/file/k13zhcc10cdf26d3455eafc6a3ae3ca7d7f0>

RUST RECONVERTERTM LT

RUST CONVERTER & PROTECTIVE COATING / PRIMER

PRODUCT HIGHLIGHTS

RUST RECONVERTER LT stops further erosion and rusting of machinery, tools, vehicles, equipment, boats, metal buildings and more.

RUST RECONVERTER LT chemically converts rust into a black organic complex while a clear acrylic coating is formed at the surface. When used indoors, the coating can last for years even without painting. When used outdoors or in high humidity applications, it should be painted over using an oil-based enamel or epoxy paint. Covers up to 500 square feet per gallon.



DIRECTIONS

NOTE: 1. SHAKE WELL BEFORE USING. 2. KEEP FROM FREEZING. Do not store at 32°F or less.

Clean rusted surface of loose rust flakes with wire brush but do not take down to bright metal. Apply by brushing, dipping, swabbing or spraying product evenly over the rusted surface. For spraying; apply using equipment designed to spray latex paint. If necessary, when spraying, add up to 3 fluid ounces of water per gallon.

Allow to dry completely prior to exposing to rain or high humidity. A clear hard finish will form. Dry time will vary depending on the temperature and humidity. Surfaces may be painted once completely dried.

WARNING: CAUSES EYE IRRITATION.

KEEP OUT OF REACH OF CHILDREN.

Contains 2-butoxyethanol and tannic acid. Wash thoroughly after handling.

FIRST AID: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

This product contains the following percentage of chemicals of unknown toxicity: 35%

See the Safety Data Sheet for additional information.

EMERGENCY TELEPHONE

USA CHEMTREC® (800) 424-9300

Outside US +1 (703) 527-3887



**CORROSION
TECHNOLOGIES**

U. S. CORROSION TECHNOLOGIES, LLC

2638 National Drive • Garland, TX 75041

800.638.7361 • FAX 972.278.9721

www.corrosionx.com

Made in the USA

PART NO. 75641



7 61866 75641 7

NET CONTENTS: 1 gallon / 3.78 liters

© 2016 U.S. Corrosion Technologies, LLC • 1M608



PRODUCT HIGHLIGHTS

RUST RECONVERTER LT stops further erosion and rusting of machinery, tools, vehicles, equipment, boats, metal buildings and more. **RUST RECONVERTER LT** chemically converts rust into a black organic complex while a clear acrylic coating is formed at the surface. When used indoors, the coating can last for years even without painting. When used outdoors or in high humidity applications, it should be painted over using an oil-based enamel or epoxy paint. Covers up to 500 square feet per gallon.

DIRECTIONS

NOTE: 1. SHAKE WELL BEFORE USING. 2. KEEP FROM FREEZING. Do not store at 32°F or less.

Clean rusted surface of loose rust flakes with wire brush but do not take down to bright metal. Apply by brushing, dipping, swabbing or spraying product evenly over the rusted surface. For spraying; apply using equipment designed to spray latex paint. If necessary, when spraying, add up to 3 fluid ounces of water per gallon.

Allow to dry completely prior to exposing to rain or high humidity. A clear hard finish will form. Dry time will vary depending on the temperature and humidity. Surfaces may be painted once completely dried.

WARNING: CAUSES EYE IRRITATION.

KEEP OUT OF REACH OF CHILDREN.

Contains 2-butoxyethanol and tannic acid. Wash thoroughly after handling.

FIRST AID: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

This product contains the following percentage of chemicals of unknown toxicity: 35%

See the Safety Data Sheet for additional information.

EMERGENCY TELEPHONE

USA CHEMTREC® (800) 424-9300

Outside US +1 (703) 527-3887



U. S. CORROSION TECHNOLOGIES, LLC
2638 National Drive • Garland, TX 75041
800.638.7361 • FAX 972.278.9721
www.corrosionx.com
Made in the USA



PART NO. 75641

7 61866 75641 7

NET CONTENTS: 1 gallon / 3.78 liters

© 2016 U.S. Corrosion Technologies, LLC • 11M008